

ARTLİNES YUNG KARO HALI

TEKNİK ÖZELLİKLER

Boyut	:50 cm x 50 cm
İplik Türü Taban	:%100 PA
Türü	:BITUMEN
İmek Yüksekliği	:4,0 mm ± 0,5 mm
Toplam Yükseklik	:6,0 mm ± 0,5 mm
İmek Ağırlığı	:550 g/m ² ± 10%
Toplam Ağırlık	:3000 g/m ² ± 10%
Alev Almazlık	:Euroclass Bfl-s1
İplik yapısı	:Bukle
Kutu İçi Karo Adeti	:20 adet (5 m ²)



Yung 01



Yung 02



Yung 03



Yung 04



Yung 05

Testing

CRIGreen	Label	Plus
Colorfastness to Light	AATCC 16-03	AATCC
Colorfastness to Water	107-02	AATCC 138-00
Colorfastness to Cleaning	AATCC 165-99	EN
Colorfastness to Crocking	985-Test A	(2001)
Change in Appearance	ISO 10361	(2015)
Change in Appearance	ISO 12951	(2020) EN
Fiber Bind - Lisson Tretrad	986	(2005)
Dimensional Change		
Side length, Squareness & Straightness		
Resistance to Fraying	EN ISO 10833	(2019)
Static Electrical propensity	ISO 6356	(2012)
Fire Classification	EN 13501-1	(2019)
Antibacterial Activity (optional)	AATCC 174-II	(2016)
Sound Absorption	ISO 354	(2003)
Thermal Resistance	ISO 8302	(1991)

ARTLİNES YUNG KARO HALI

